



SAFETY DATA SHEET SUPER RUSCON

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010According to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SUPER RUSCON

Product number 0150 - 0141

Synonyms; trade names 10685 (Internal Ref)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier Dacrylate Paints Ltd,

Lime Street, Kirkby-in-Ashfield Nottingham NG17 8AL Tel: +44 (0) 1623-753845 Fax: +44 (0) 1623-757151

Contact person sales@dacrylate.co.uk

1.4. Emergency telephone number

National emergency telephone +44 (0) 1623 753845 08:30-17:00 MON-FRI

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Human health Prolonged skin contact may cause temporary irritation.

Environmental This product is not regarded as a health or environmental hazard under current legislation.

See Classification, Labelling and Risk Information.

Physicochemical See Section 7.2 Storage Class. See Section 5.2 Hazardous combustion products. See

Section 10: Stability and reactivity

2.2. Label elements

Hazard statements NC Not Classified

SUPER RUSCON

Precautionary statements P102 Keep out of reach of children.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

OXALIC ACID 1-5%

CAS number: 144-62-7 EC number: 205-634-3

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Xn;R21/22

Acute Tox. 4 - H312

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Ingredient notesThis product is not regarded as a health or environmental hazard under current legislation.

See Classification, Labelling & Risk Information This product contains a preservative. May

cause an allergic reaction.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information The severity of the symptoms described will vary depending on the concentration and the

length of exposure. Move affected person to fresh air and keep warm and at rest in a position

comfortable for breathing.

Inhalation Get medical attention. Place unconscious person on their side in the recovery position and

ensure breathing can take place. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention. Symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Show this Safety Data

Sheet to the medical personnel.

Ingestion Remove affected person from source of contamination. Rinse mouth thoroughly with water.

Give plenty of water to drink. DO NOT induce vomiting. Get medical attention immediately.

Skin contact Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur

after washing. Use barrier creams to prevent skin contact. Remove contaminated clothing and

rinse skin thoroughly with water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after

washing. Show this Safety Data Sheet to the medical personnel.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. In case

of insufficient ventilation, wear suitable respiratory equipment.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Harmful if inhaled Vapours may cause headache, fatigue, dizziness and nausea.

SUPER RUSCON

Ingestion Harmful if swallowed. May cause nausea, stomach pain and vomiting.

Skin contact Skin irritation. May cause sensitisation or allergic reactions in sensitive individuals.

Eye contact May cause severe eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

No specific recommendation given, but first aid may still be required in case of accidental

exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY! In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Notes:

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire. Extinguish with foam, carbon

dioxide or dry powder.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards The pressure in sealed containers can increase under the action of heat. The material will not

support combustion unless the water has evaporated.

Hazardous combustion

products

In case of fire, toxic gases (CO, CO2, NOx) may be formed. Acrid smoke or fumes. Other pyrolysis products typical of burning an organic material. Harmful gases or vapours.

Protection against nuisance dust must be used when the airborne concentration exceeds 10

mg/m3. In the event of a fire and/or explosion, do not breathe fumes.

5.3. Advice for firefighters

Protective actions during

firefighting

Keep up-wind to avoid fumes. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Containers close to fire should be removed or cooled with water. If risk of water pollution occurs, notify appropriate authorities. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken without appropriate training or involving any personal risk.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet. Do not handle broken packages without protective equipment. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Where anti slip aggregates, powders or similar are added/post added to a paint, the potential for the generation of respirable dust during handling and use can occur. In such cases, occupational exposures to respirable dust should be monitored and controlled. In the case of exposure to prolonged or high levels of air borne dust, wear a personal respirator in compliance with national legislation. No smoking, sparks, flames or other sources of ignition near spillage.

SUPER RUSCON

For non-emergency personnel Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate

ventilation. Wear suitable respirator when ventilation is inadequate. Put on appropriate personal protective equipment. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel

from entering.

For emergency responders If specialised clothing is required to deal with the spillage, take note of any information in

Section 8 on suitable materials. See also the information in "For non-emergency personnel".

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

No smoking, sparks, flames or other sources of ignition near spillage. Absorb spillage with inert, damp, non-combustible material. Flush contaminated area with plenty of water. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. If involved in a fire, shut off flow if it can be done without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Small Spillages: Absorb small quantities with paper towels and evaporate in a safe place. Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers. The accumulation of contaminated rags and application cloths may result in spontaneous combustion. This is particularly important in the case of products containing a high level of drying oils such as teak oil, linseed oil etc. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards.

6.4. Reference to other sections

Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions No specific recomme

No specific recommendations. Observe good housekeeping practices. Avoid contact with skin and eyes. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. All handling should only take place in well-ventilated areas.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate hand lotion to prevent defatting and cracking of skin.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Protect from freezing and direct sunlight. Store in tightly-closed, original container in a dry,

cool and well-ventilated place. Store at temperatures between 5°C and 35°C (32 to 95°F). Containers which have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate containment to avoid environmental contamination. Avoid/separate

from oxidising agents. Observe the label precautions.

Storage class Not Applicable

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2. Restricted to professional

users.

SUPER RUSCON

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

OXALIC ACID

Long-term exposure limit (8-hour TWA): WEL 1 mg/m³ Short-term exposure limit (15-minute): WEL 2 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment







When spraying, the use of a suitable/approved respirator is advised. Note:

Appropriate engineering

controls

No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

Personal protection Advice on personal protection is applicable for high exposure levels. Select proper personal

protection based on a risk assessment of the actual exposure scenario.

Eye/face protection The following protection should be worn: Chemical splash goggles. Eyewear complying with

an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

> a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves

Wear appropriate clothing to prevent reasonably probable skin contact. Use barrier creams to

should comply with European Standard EN374.

Other skin and body protection

prevent skin contact.

Hygiene measures Use engineering controls to reduce air contamination to permissible exposure level. Provide

> eyewash station and safety shower. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when handling this product.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory

protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable

for its intended use and is 'CE'-marked.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Notes:

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid. Colour Beige.

SUPER RUSCON

Odour Almost odourless.

Odour threshold Not determined.

pH Not determined.

Melting point Not determined.

Initial boiling point and range Not determined.

Flash point Not applicable.

Evaporation rate Not determined.

Evaporation factor Not determined.

Flammability (solid, gas) No specific test data are available.

Upper/lower flammability or

explosive limits

Not applicable.

Other flammability No specific test data are available.

Vapour pressure Not determined.

Vapour density Not determined.

Relative density 0.95 - 1.05 @ 20°C

Bulk density Not determined.

Solubility(ies) Miscible with water.

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity Not determined.

Explosive properties Not considered to be explosive.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties Not determined.

9.2. Other information

Other information Paints are dilutable with water. Store at temperatures above 5°C (32°F). Protect from freezing.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Further information

on correct storage: refer to Section 7.

10.3. Possibility of hazardous reactions

Possibility of hazardous

None under normal processing

reactions

10.4. Conditions to avoid

SUPER RUSCON

Conditions to avoid Avoid freezing. Avoid heat, flames and other sources of ignition. Do not pressurise, cut, weld,

braze, solder, drill, grind or expose containers to conditions to heat or sources of ignition. Avoid extremes of temperature and direct sunlight. Protection against nuisance dust must be

used when the airborne concentration exceeds 10 mg/m3.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO2). Oxides of nitrogen. Acrid smoke or fumes. In

case of fire and/or explosion, do not breaths fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 10,020.04

Acute toxicity - dermal

ATE dermal (mg/kg) 22,044.09

General information This product is unlikely to harm health, given normal and proper handling and hygienic

precautions. Prolonged and repeated contact with solvents over a long period may lead to

permanent health problems.

Inhalation Irritating to respiratory system.

Ingestion Irritating. May cause nausea, stomach pain and vomiting.

Skin contact Repeated exposure may cause skin dryness and cracking.

Eye contact Irritating to eyes.

Route of entry Inhalation Ingestion. Skin and/or eye contact

Additional Information: For further information, please refer to Sections 4 and 8 respectively.

Toxicological information on ingredients.

OXALIC ACID

Acute toxicity - oral

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

ATE dermal (mg/kg) 1,100.0

Serious eye damage/irritation

Serious eye Harmful in contact with eyes and skin. Irritating to eyes.

damage/irritation

Respiratory sensitisation

Respiratory sensitisation Irritating to respiratory system.

Skin sensitisation

Skin sensitisation Not sensitising. Mildly irritating.

SUPER RUSCON

Germ cell mutagenicity

Genotoxicity - in vitroNo information available.

Genotoxicity - in vivoNo specific test data are available.

Carcinogenicity

Carcinogenicity No specific test data are available.

Reproductive toxicity

Reproductive toxicity -

fertility

No specific test data are available.

Reproductive toxicity -

development

No information available.

Specific target organ toxicity - single exposure

STOT - single exposure No specific test data are available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No specific test data are available.

Aspiration hazard

Aspiration hazard No information available.

General information This product is unlikely to harm health, given normal and proper handling and

hygienic precautions. Prolonged and repeated contact with solvents over a long

period may lead to permanent health problems.

Inhalation Harmful by inhalation.

Ingestion Harmful if swallowed.

Skin contact Harmful in contact with skin. Irritating to skin.

Eye contact Harmful in contact with eyes. Irritating and may cause redness and pain.

Route of entry Ingestion Inhalation Oral Skin and/or eye contact

SECTION 12: Ecological Information

Ecotoxicity The product may affect the acidity (pH) of water which may have hazardous effects on aquatic

organisms.

12.1. Toxicity

Toxicity The product components are not classified as environmentally hazardous. However, this does

not exclude the possibility that large or frequent spills can have a harmful or damaging effect

on the environment.

12.2. Persistence and degradability

Persistence and degradability This substance is not readily degradeable.

Biodegradation Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential Not known.

Partition coefficient Not determined.

SUPER RUSCON

12.4. Mobility in soil

Mobility The product is water-soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. The generation of waste should be minimised or avoided wherever possible. The company encourages the recycle, recovery and reuse of materials,

wherever possible.

Disposal methods Avoid the spillage or runoff entering drains, sewers or watercourses. Residues and empty

containers should be taken care of as hazardous waste according to local and national provisions. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor. Dispose of contents/container in accordance with local regulations. Waste product should not be discharged directly into drains or water courses without treatment, chemical precipitation/flocculation. Remove the clear supernatant and flush to a chemical sewer. The precipitate is not hazardous. Dispose at a permitted facility

in accordance with local and national regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SUPER RUSCON

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Petroleum (Consolidation) Act, as amended 1984 SI 1244.

Highly Flammable Liquid Regulations 1972. Rivers (Prevention of Pollution) Act 1961.

Control of Pollution (Special Waste) Regulations 1980 (as amended).

Control of Substances Hazardous to Health Regulations 2002 (as amended).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Commission Regulation (EU) No 453/2010 of 20 May 2010.

Guidance Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG228.

Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Recommended storage between 5°C and 35°C. Protect from direct sunlight. Keep out of

reach of children.

Issued by MW

Revision date 13/07/2017

Revision 1

SDS number 10685

Risk phrases in full Not classified.

R21/22 Harmful in contact with skin and if swallowed.

Hazard statements in full H302 Harmful if swallowed.

H312 Harmful in contact with skin.

The product should not be used for the purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.