

**PRODUCT DATA SHEET****05/2024**

|                                   |   |                                  |
|-----------------------------------|---|----------------------------------|
| <b>Product Name</b>               | <b>Road/Line Marking Paint</b>  |                                  |
| <b>Our Reference</b>              | <b>4980 Line</b>  |                                  |
| <b>Description</b>                | Quick drying, durable, long lasting line marking paint for interior and exterior use. Car parks, factory floors.                          |                                  |
| <b>Colours</b>                    | Yellow 4980-2-7, White 4980-6-3   |                                  |
| <b>Gloss Level</b>                | Eggshell (10-15% gloss)   |                                  |
| <b>Theoretical Spreading Rate</b> | 8 sq m per litre at 40 microns dry film thickness (d.f.t) per coat. Coverage depends on porosity of substrate. 2 coats normally required. |                                  |
| <b>Drying Time 20°C</b>           | Touch dry: 30 minutes at 20°C   |                                  |
| <b>Application</b>                | <b>Brush/roller</b>   | Apply as supplied                |
|                                   | <b>Conventional Spray</b>   | Thin up to 20% with BT1 thinner. |
| <b>Overcoating</b>                | Can be overcoated at any time.  |                                  |
| <b>Surface Preparation</b>        | Surfaces must be clean and dry.   |                                  |
| <b>Packaging</b>                  | 5 litres  |                                  |
| <b>Thinner</b>                    | BT1 (thinning) BT2 (cleaning)   |                                  |
| <b>VOC (supplied)</b>             | 500-550 grams per litre   |                                  |