



# SAFETY DATA SHEET THINNERS R5

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010, According to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier		
Product name	THINNERS R5	
Product number	0500-TR05	
1.2. Relevant identified uses o	f the substance or mixture and uses advised against	
Identified uses	Solvent/Thinner	
1.3. Details of the supplier of the	ne safety data sheet	
Supplier	Dacrylate Paints Ltd, Lime Street, Kirkby-in-Ashfield Nottingham NG17 8AL Tel: +44 (0) 1623-753845 Fax: +44 (0) 1623-757151	
Contact person	sales@dacrylate.co.uk	
1.4. Emergency telephone nur	nber	
National emergency telephone +44 (0) 1623 753845 08:30-17:00 MON-FRI number		
SECTION 2: Hazards identifica	ation	
SECTION 2: Hazards identification of the substant		
2.1. Classification of the substa	ance or mixture	
2.1. Classification of the substaction Classification Physical hazards	ance or mixture Flam. Liq. 3 - H226	
2.1. Classification of the substaction Classification Physical hazards Health hazards	ance or mixture Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	
2.1. Classification of the substaction Classification Physical hazards	ance or mixture Flam. Liq. 3 - H226	
2.1. Classification of the substaction Classification Physical hazards Health hazards	ance or mixture Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Not Classified	
2.1. Classification of the substa <u>Classification</u> Physical hazards Health hazards Environmental hazards Classification (67/548/EEC or	ance or mixture Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Not Classified	
2.1. Classification of the substa <u>Classification</u> Physical hazards Health hazards Environmental hazards Classification (67/548/EEC or 1999/45/EC)	Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Not Classified Xn;R20/21. Xi;R38. R10. Prolonged and repeated contact with solvents over a long period of time may lead to	
2.1. Classification of the substa <u>Classification</u> Physical hazards Health hazards Environmental hazards Classification (67/548/EEC or 1999/45/EC) Human health	ance or mixture         Flam. Liq. 3 - H226         Acute Tox. 4 - H332 Skin Irrit. 2 - H315         Not Classified         Xn;R20/21. Xi;R38. R10.         Prolonged and repeated contact with solvents over a long period of time may lead to permanent health problems.         The majority of solvents are volatile. Provide adequate ventilation to reduce build up of solvent	

### Pictogram





•	
Signal word	Warning
Hazard statements	H226 Flammable liquid and vapour. H315 Causes skin irritation. H332 Harmful if inhaled.
Precautionary statements	<ul> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P280 Wear protective gloves/protective clothing/eye protection/face protection.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.</li> <li>Rinse skin with water/shower.</li> <li>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</li> <li>P332+P313 If skin irritation occurs: Get medical advice/attention.</li> <li>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</li> <li>P403+P235 Store in a well-ventilated place. Keep cool.</li> <li>P501 Dispose of contents/container in accordance with national regulations.</li> </ul>
Contains	XYLENE
Supplementary precautionary statements	<ul> <li>P233 Keep container tightly closed.</li> <li>P240 Ground/bond container and receiving equipment.</li> <li>P241 Use explosion-proof electrical equipment.</li> <li>P242 Use only non-sparking tools.</li> <li>P243 Take precautionary measures against static discharge.</li> <li>P261 Avoid breathing vapour/spray.</li> <li>P264 Wash contaminated skin thoroughly after handling.</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P302+P352 IF ON SKIN: Wash with plenty of water.</li> <li>P312 Call a POISON CENTER/doctor if you feel unwell.</li> <li>P321 Specific treatment (see medical advice on this label).</li> <li>P362+P364 Take off contaminated clothing and wash it before reuse.</li> </ul>

## 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

3.2. Mixtures		
XYLENE		60-100%
CAS number: 1330-20-7	EC number: 215-535-7	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xn;R20/21 Xi;R38	
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

General information	The severity of the symptoms described will vary depending on the concentration and the length of exposure. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.	
Inhalation	Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention. Symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Show this Safety Data Sheet to the medical personnel.	
Ingestion	Remove affected person from source of contamination. Rinse mouth thoroughly with water. Give plenty of water to drink. DO NOT induce vomiting. Get medical attention immediately.	
Skin contact	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing. Use barrier creams to prevent skin contact. Remove contaminated clothing and rinse skin thoroughly with water.	
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.	
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. In case of insufficient ventilation, wear suitable respiratory equipment.	
4.2. Most important symptoms	and effects, both acute and delayed	
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.	
Inhalation	Harmful if inhaled Vapours may cause headache, fatigue, dizziness and nausea.	
Ingestion	Harmful if swallowed. May cause nausea, stomach paint and vomiting.	
Skin contact	Skin irritation. May cause sensitisation or allergic reactions in sensitive individuals.	
Eye contact	May cause severe eye irritation.	
4.3. Indication of any immedia	te medical attention and special treatment needed	
Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
SECTION 5: Firefighting meas	sures	
5.1. Extinguishing media		
Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire. Extinguish with foam, carbon dioxide or dry powder.	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
5.2. Special hazards arising fr	om the substance or mixture	
Specific hazards	Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. If a fire or if heated, a pressure increase will occur and the container may burst with the risk of subsequent explosion. The product is flammable.	

Hazardous combustion products	In case of fire, toxic gases (CO, CO2, NOx) may be formed. Acrid smoke or fumes. Other pyrolysis products typical of burning an organic material. In case of fire, toxic gases (CO, CO2, NOx) may be formed. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. In the event of a fire and/or explosion, do not breathe fumes.
5.3. Advice for firefighters	
Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material. Keep up-wind to avoid fumes. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken without appropriate training or involving any personal risk.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
SECTION 6: Accidental releas	e measures
6.1. Personal precautions, prot	tective equipment and emergency procedures
Personal precautions	Do not handle broken packages without protective equipment. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Wash thoroughly after dealing with a spillage. No smoking, sparks, flames or other sources of ignition near spillage.
For non-emergency personnel	Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear suitable respirator when ventilation is inadequate. Put on appropriate personal protective equipment. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable materials. See also the information in "For non-emergency personnel".
6.2. Environmental precautions	S
Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
6.3. Methods and material for o	containment and cleaning up
Methods for cleaning up	No smoking, sparks, flames or other sources of ignition near spillage. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. If involved in a fire, shut off flow if it can be done without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Small Spillages: Absorb small quantities with paper towels and evaporate in a safe place. Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers. The accumulation of contaminated rags and application cloths may result in spontaneous combustion. This is particularly important in the case of products containing a high level of drying oils such as teak oil, linseed oil etc. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards.
6.4. Reference to other section	
Reference to other sections	Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see section 13.
SECTION 7: Handling and stor	rage

### 7.1. Precautions for safe handling

Usage precautions	Avoid contact with skin and eyes. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. All handling should only take place in well-ventilated areas. Dust may form explosive mixture with air. Take precautionary measures against static discharges. Storage tanks and other containers must be earthed. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used.	
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate hand lotion to prevent defatting and cracking of skin.	
7.2. Conditions for safe storage, including any incompatibilities		
Storage precautions	Keep away from oxidising materials, heat and flames. Keep container tightly closed and in a well-ventilated place. Avoid/separate from strong acids, alkalis, oxidising and reducing agents. Observe the label precautions. Containers which have been opened must be carefully resealed and kept upright to prevent leakage.	
Storage class	Flammable liquid storage.	
7.3. Specific end use(s)		
Specific end use(s)	The identified uses for this product are detailed in Section 1.2. Restricted to professional users.	

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

### Occupational exposure limits

### **XYLENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m3(Sk)

WEL = Workplace Exposure Limit

Ingredient comments

WEL = Workplace Exposure Limits

## XYLENE (CAS: 1330-20-7)

#### DNEL

- Inhalation; Short term : 442 mg/m<sup>3</sup>

### 8.2. Exposure controls



Note:

Appropriate engineering controls

Eye/face protection

When spraying, the use of a suitable/approved respirator is advised.

No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

The following protection should be worn: Chemical splash goggles. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374.
Other skin and body protection	Wear appropriate clothing to prevent skin contamination. Use barrier creams to prevent skin contact.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Provide eyewash station and safety shower. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Keep container tightly sealed when not in use.

# SECTION 9: Physical and Chemical Properties

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	Characteristic/of solvents
Odour threshold	Not determined.
рН	Not relevant.
Melting point	~ -39°C
Initial boiling point and range	~ 138°C°C @ 760 mm Hg
Flash point	27 - 32°C
Evaporation rate	0.70
Evaporation factor	Not determined.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.8% Upper flammable/explosive limit: 7%
Other flammability	Not known.
Vapour pressure	7.00 @ °C
Vapour density	3.70
Relative density	0.86 ± 0.05 @ 20°C
Bulk density	Not determined.
Solubility(ies)	Soluble in the following materials: Organic solvents.
Partition coefficient	Not available.

Auto-ignition temperature	465°C	
Decomposition Temperature	Not determined.	
Viscosity	Not determined.	
Explosive properties	May form explosive mixtures with air.	
Explosive under the influence of a flame	Not considered to be explosive.	
Oxidising properties	Not determined.	
Comments	Information given is applicable to the product as supplied.	
9.2. Other information		
Other information	None.	
SECTION 10: Stability and rea	ictivity	
10.1. Reactivity		
Reactivity	The following materials may react with the product: Acids. Alkalis. Oxidising materials.	
10.2. Chemical stability		
Stability	Stable at normal ambient temperatures and when used as recommended. Further information on correct storage: refer to Section 7.	
10.3. Possibility of hazardous	reactions	
Possibility of hazardous reactions	None under normal processing Vapours may form explosive mixtures with air.	
10.4. Conditions to avoid		
Conditions to avoid	Avoid contact with strong oxidising agents. Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to conditions to heat or sources of ignition. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Avoid extremes of temperature and direct sunlight.	
10.5. Incompatible materials		
Materials to avoid	Strong oxidising agents.	
10.6. Hazardous decompositio	in products	
Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO2). Oxides of nitrogen. Acrid smoke or fumes. In case of fire and/or explosion, do not breaths fumes.	
SECTION 11: Toxicological information		
11.1. Information on toxicologi	cal effects	
Acute toxicity - dermal ATE dermal (mg/kg)	2,000.20002	
<u>Acute toxicity - inhalation</u> ATE inhalation (vapours mg/l)	11.00110011	
General information	This product is unlikely to harm health, given normal and proper handling and hygienic precautions. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.	

Inhalation	Harmful by inhalation. Irritating to respiratory system.
Ingestion	Irritating. May cause nausea, stomach pain and vomiting.
Skin contact	Harmful in contact with skin. Irritating to skin.
Eye contact	Harmful in contact with eyes. Irritating to eyes.
Acute and chronic health hazards	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Nausea, vomiting. Headache. Gas or vapour may irritate the respiratory system. Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema. EYES, NOSE AND MOUTH. Repeated exposure may cause chronic eye irritation. SKIN. Mild dermatitis, allergic skin rash.
Route of entry	Inhalation Ingestion. Skin and/or eye contact Oral
Additional Information:	For further information, please refer to Sections 4 and 8 respectively
Toxicological information on ingredients.	

## <u>XYLENE</u>

Toxicological effects	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. High vapour concentrations can cause headaches, dizziness and nausea.
Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	4,300.0
Species	Rat
Acute toxicity - dermal	
Acute toxicity dermal (LD₅ mg/kg)	2,000.0
Species	Rabbit
ATE dermal (mg/kg)	2,000.0
Acute toxicity - inhalation	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	11.0
Species	Rat
ATE inhalation (vapours mg/l)	11.0
Skin corrosion/irritation	
Animal data	No information available.
Human skin model test	Irritating.
Serious eye damage/irritati	on
Serious eye damage/irritation	Causes eye irritation
Respiratory sensitisation	

Respiratory sensitisation	There is no evidence that the product can cause respiratory hypersensitivity.
Skin sensitisation	
Skin sensitisation	No information available.
Germ cell mutagenicity	
Genotoxicity - in vitro	Negative.
Genotoxicity - in vivo	Negative.
Carcinogenicity	
Carcinogenicity	No evidence of carcinogenicity
Reproductive toxicity	
Reproductive toxicity - fertility	This substance has no evidence of toxicity to reproduction.
Reproductive toxicity - development	No information available.
Specific target organ toxicit	y - single exposure
STOT - single exposure	Central and/or peripheral nervous system damage.
Target organs	Central nervous system Liver Kidneys
Specific target organ toxicit	y - repeated exposure
STOT - repeated exposure	No information available.
Aspiration hazard	
Aspiration hazard	Aspiration hazard if swallowed.
General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Harmful by inhalation.
Ingestion	Irritating. May cause nausea, stomach pain and vomiting.
Skin contact	Harmful in contact with skin. Irritating to skin.
Eye contact	The product is irritating to eyes and skin.
Route of entry	Oral Skin and/or eye contact Inhalation Ingestion
Target organs	Central nervous system
Medical symptoms	Allergies. Irritation of eyes and mucous membranes. Headache. Fatigue. Dizziness.
12: Ecological Information	

# SECTION 12: Ecological Information

## Ecotoxicity

Large quantities of the product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

## 12.1. Toxicity

## Ecological information on ingredients.

## XYLENE

assessment

Toxicity		The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Acute toxicity - fi	sh	, LC50 96 hours 4200 ug/lt (Rainbow Trout):,
Acute toxicity - aquatic invertebrates		, EC50 48 hours 2930-4400 ug/lt (Daphnia magma):,
Acute toxicity - aquatic plants		No information available.
Acute toxicity - microorganisms		, IC50, 72 hours, Algae, mg/lt 2.2:,
Acute toxicity - terrestrial		No information available.
12.2. Persistence and degrad	ability	
Persistence and degradability	There a	re no data on the degradability of this product.
Biodegradation	Not dete	ermined.
Ecological information on ingr	edients.	
		XYLENE
Persistence and degradability		The product is readily biodegradable.
Biodegradation		The substance is readily biodegradable.
12.3. Bioaccumulative potentia	al	
Bioaccumulative potential	The pro	duct does not contain any substances expected to be bioaccumulating.
Partition coefficient	Not ava	ilable.
Ecological information on ingr	edients.	
		XYLENE
Bioaccumulative	potential	The product does not contain any substances expected to be bioaccumulating.
Partition coefficie	ent	No information available.
12.4. Mobility in soil		
Mobility	The pro	duct is insoluble in water and will spread on the water surface.
Ecological information on ingr	edients.	
		XYLENE
Mobility		The product is partly soluble in water and may spread in the aquatic environment. Predicted to have mobility in soil. The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
12.5. Results of PBT and vPv	B assessn	nent
Results of PBT and vPvB	This pro	duct does not contain any substances classified as PBT or vPvB.

### Ecological information on ingredients.

XYLENE

**Results of PBT and vPvB** This product does not contain any substances classified as PBT or vPvB. assessment

### 12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal	considerations
----------------------	----------------

## 13.1. Waste treatment methods

General information	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. This material and its container must be disposed of in a safe way. The generation of waste should be minimised or avoided wherever possible. The company encourages the recycle, recovery and reuse of materials, wherever possible.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Avoid the spillage or runoff entering drains, sewers or watercourses. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Dispose of waste via a licensed waste disposal contractor. Dispose of contents/container in accordance with national regulations.

## **SECTION 14: Transport information**

General	To avoid the risk of spillage, always store and transport in a secure, upright position. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	
14.1. UN number		
UN No. (ADR/RID)	1307	
UN No. (IMDG)	1307	
UN No. (ICAO)	1307	
UN No. (ADN)	1307	
14.2. UN proper shipping name	9	
Proper shipping name (ADR/RID)	XYLENES	
Proper shipping name (IMDG)	XYLENES	
Proper shipping name (ICAO)	XYLENES	
Proper shipping name (ADN)	XYLENES	
14.3. Transport hazard class(es)		
ADR/RID class	3	
ADR/RID classification code	F1	
ADR/RID label	3	
IMDG class	3	
ICAO class/division	3	
ADN class	3	

### Transport labels



14.4. Packing group	
ADR/RID packing group	Ш
IMDG packing group	Ш
ADN packing group	Ш
ICAO packing group	Ш
14.5. Environmental hazards	

## Environmentally hazardous substance/marine pollutant

No.

## 14.6. Special precautions for user

EmS	F-E, S-D
ADR transport category	3
Emergency Action Code	3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

## SECTION 15: Regulatory information

National regulations	Petroleum (Consolidation) Act, as amended 1984 SI 1244.
	Highly Flammable Liquid Regulations 1972.
	Rivers (Prevention of Pollution) Act 1961.
	Control of Pollution (Special Waste) Regulations 1980 (as amended).
	Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18
	December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16
	December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
	Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work (as amended).
	Commission Regulation (EU) No 453/2010 of 20 May 2010.

### Guidance

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131. Safety Data Sheets for Substances and Preparations.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### **SECTION 16: Other information**

General information	Product to be used in industrial and/or professional applications.
Issued by	BOD
Revision date	06/03/2015
Revision	0
SDS number	10033
Risk phrases in full	R10 Flammable. R20/21 Harmful by inhalation and in contact with skin. R38 Irritating to skin.
Hazard statements in full	H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H332 Harmful if inhaled.

The product should not be used for the purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.