



# Safety Data Sheet

## According to Regulation (EC) No. 1907/2006 (REACH)

## GUNCLEANER/DEGREASER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifier** 

> Product name: GUNCLEANER/DEGREASER

Product code: BT2

**Product description:** Degreaser and gun cleaner.

CAS No.: Not applicable. EC No.: Not applicable. Index No.: Not applicable.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s): Degreasing and spray-gun cleaning.

Uses advised against: Follow supplier's recommendations on correct use of the

product.

1.3 Details of the supplier of the safety data sheet

> Manufacturer/Supplier: S G Bailey Paints Limited

> > Unit 15A Griffin Mill London Road Thrupp

Stroud

Gloucestershire

GL5 2AZ

Telephone: +44 (0)1453 882237

E-mail: richard@baileypaints.co.uk

1.4 **Emergency telephone number** 

> In case of emergency, call: +44 (0) 7774 460658 (UK number, 24 hours, 7 days)

Version: 1.0 Product code: BT2 Page 1 of 14 Date: 06/01/2017





# Safety Data Sheet

## According to Regulation (EC) No. 1907/2006 (REACH)

## **SECTION 2: Hazard Identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 (CLP)

Flammable Liquid 2; H225

Skin Irritant 2; H315

Eye Irritant 2; H318

Acute Toxicity 4; H312

Acute Toxicity 4; H332

Specific Target Organ Toxicity Single Exposure 3; H335

Specific Target Organ Toxicity Single Exposure 3; H336

Specific Target Organ Toxicity Repeated Exposure 2; H373

Aspiration Toxicity 1, H304

## 2.2 Label elements according to Regulation (EC) No. 1272/2008 (CLP)

#### Hazard pictogram(s):



Signal Word: Danger

**Hazard Statement(s):** H225: Highly flammable liquid and vapour.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness and dizziness.

H373: May cause damage to organs through prolonged

or repeated exposure.

H304: May be fatal if swallowed and enters airways.

Precautionary Statement(s): P210: Keep away from heat / sparks / open flames / hot

surfaces. No smoking.

Version: 1.0 Product code: BT2 Page 2 of 14
Date: 06/01/2017 Product name: Guncleaner/Degreaser





P260: Do not breathe vapours.

P280: Wear protective gloves / protective clothing / eye

protection / face protection.

P302 + P352: IF ON SKIN: Wash with plenty of soap

and water.

P301 + P310: IF SWALLOWED: Immediately call a

doctor/physician.

P331: Do NOT induce vomiting.

P305 + P351 + P338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P501: Dispose of contents/container to hazardous

waste.

**Supplemental Hazard information** 

(EU): None

Contains: Isopropanol, Xylene, Ethylbenzene, Methyl ethyl ketone

#### 2.3 Other hazards:

Product may charge electrostatically.

## **SECTION 3: Composition**

#### 3.2 Mixtures

Version: 1.0

Date: 06/01/2017

### Classification according to Regulation (EC) No. 1272/2008 (CLP)

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Xylene  REACH Registration no.: 01-2119488216-32	40 - 72	1330-20-7	215-535-7	601-022-00-9	Flam. Liq. 3; H226 Acute Tox. 4; H312 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE3; H335 STOT RE2; H373 Asp. Tox. 1; H304
Isopropanol  REACH Registration no.: 01-2119457588-25-xxxx	19	67-63-0	200-661-7	603-177-00-0	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Ethylbenzene	11	100-41-4	202-849-4	601-023-00-4	Flam. Liq. 2; H225 Acute Tox. 4; H332

Product code: BT2
Product name: Guncleaner/Degreaser





Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Methyl ethyl ketone  REACH Registration no.: 01-2119457290-43	10	78-93-3	201-159-0	606-002-00-3	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

See Section 16 for full description of H statements.

## **SECTION 4: First Aid Measures**

#### 4.1 Description of first aid measures

INHALATION: Remove patient to fresh air and keep at rest. If there

are breathing problems, seek medical advice.

**SKIN CONTACT:** Remove contaminated clothing immediately. Wash

affected area with copious amounts of soap and water.

Seek medical advice if symptoms persist.

**EYE CONTACT:** Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do.

Continue rinsing. Seek medical advice.

**INGESTION:** Give small quantities of water to drink. Do NOT induce

vomiting. Obtain immediate medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

Serious eye irritation, skin irritation, respiratory irritation. May cause drowsiness or dizziness.

## 4.3 Indication of any immediate medical attention and special treatments needed

If ingested, product may be aspirated into the lungs and cause chemical pneumonitis. Treat symptomatically.

## **SECTION 5: Fire-fighting Measures**

#### 5.1 Extinguishing Media

**Suitable extinguishing media:** Foam, CO<sub>2</sub> or dry powder.

**Unsuitable extinguishing media:** Do not use water jet.

Version: 1.0 Product code: BT2 Page 4 of 14

Date: 06/01/2017 Product name: Guncleaner/Degreaser





#### 5.2 Special hazards arising from the substance or mixture

Vapours may be heavier than air and may travel along the ground to a distant ignition source and flash back, causing fire or explosion. Containers may rupture on heating. Toxic gases may be formed in a fire.

#### 5.3 Advice for fire-fighters

FLAMMABLE. Evacuate area. Prevent run-off from fire control or dilution from entering drains or water courses. Self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep fire-exposed containers cool by spraying with water. Do not allow to enter drains, sewers or watercourses.

Flash point: 19°C.

## **SECTION 6: Accidental Release Measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

Eliminate sources of ignition. Ensure adequate ventilation. Avoid contact with skin and eyes. Avoid inhalation of vapours. Wear suitable personal protective equipment. Wear appropriate respirator when ventilation is inadequate (see Section 8).

#### 6.1.2 For emergency responders

Keep unnecessary personnel away. Wear suitable protective clothing (see Section 8). Contaminated clothing should be thoroughly cleaned.

#### 6.2 **Environmental precautions**

Collect spillage. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

#### 6.3 Methods and materials for containment and clearing up

#### 6.3.1 For containment

Stop the leak if it is safe to do so. Contain the spillage with sand, earth or any suitable adsorbent material.

Version: 1.0 Product code: BT2 Page 5 of 14 Date: 06/01/2017





#### 6.3.2 For cleaning up

Use sand, earth or any suitable non-combustible adsorbent material to adsorb spillages. Using non-sparking tools transfer the contaminated absorbent material into sealable containers for disposal. Containers should be sealed before being disposed of via an authorised waste disposal contractor.

#### 6.3.3 Other advice

None

#### Reference to other sections 6.4

See Section 8 for personal protective equipment. See Section 13 for waste disposal.

## **SECTION 7: Handling and Storage**

#### 7.1 Precautions for safe handling

Provide adequate ventilation, including local extraction to ensure the occupational exposure limit is not exceeded. Do not inhale vapours. Avoid contact with skin and eyes. Wear suitable personal protective equipment (see Section 8). Eliminate all sources of ignition. Electrical equipment should be protected to the appropriate standard.

Do not eat, drink or smoke when using this product. Wash exposed skin after use. Contaminated work clothing should not be allowed out of the workplace. Contaminated clothing should be thoroughly cleaned or disposed of as hazardous waste.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Keep from direct sunlight. Store locked up. Store only in the original container. Do not pressurise container. Product may charge electrostatically so all containers and associated equipment should be earthed and bonded to prevent static charge accumulation. Store in a cool, well ventilated place. Empty containers retain product residue and can be hazardous.

Ensure compliance with all regulations and guidance associated with the storage and use of flammable liquids.

See section 10 for incompatible materials.

#### 7.3 Specific end uses(s)

Degreaser and spray-gun cleaner.

Version: 1.0 Product code: BT2 Page 6 of 14 Date: 06/01/2017





## **SECTION 8: Exposure Controls/Personal Protection**

#### 8.1 **Control parameters**

### Workplace exposure limits (WEL) - United Kingdom

Source: EH40/2005, 2nd Ed., 2011

Substance	CAS no.	LTEL (8	3 hr TWA)	STEL (15 min)		
Oubstance	OAO IIO.	ppm	mg/m³	ppm	mg/m³	
Xylene	1330-20-7	50	220	100	441	
Ethylbenzene	100-41-4	100	441	125	552	
Methyl ethyl ketone	78-93-3	200	600	300	899	
Isopropanol	67-63-0	400	999	500	1250	

### Other exposure limits

Consult applicable national legislation for WELs in other countries.

### **Biological limits**

Substance	Specimen	Sampling time	Limit	Determinant	Source
Xylene	Creatinine in urine	End of shift	650 mmol/mol	Methyl hippuric acid	UK BMGV

## Derived No-Effect Level (DNEL) - industry

Substance	Dermal	Inhalation	Oral
Xylene	Long-term: 3182 mg/kg/day	Short-term: 442 mg/m <sup>3</sup> Long-term: 180 mg/kg/day	Not available
Methyl ethyl ketone	1 day: 1161 mg/kg	600 mg/m <sup>3</sup>	Not available

Version: 1.0 Product code: BT2 Page 7 of 14 Date: 06/01/2017





#### **Predicted No-Effect Concentration (PNEC)**

Substance	Aqua (fresh water)	Aqua (marine water)	Aqua (intermitt ent releases)	Sewage Treatment Plants	Sediment	Soil	Oral (secondary poisoning)
Xylene	0.327 mg/l	0.327 mg/l	0.327 mg/l	6.58 mg/l	12.46 mg/kg dwt	2.31 mg/kg	-
Methyl ethyl ketone	55.8 mg/l	-	-	-	-	22.5 mg/kg	-

#### 8.2 **Exposure controls**

#### 8.2.1 Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction. Electrical equipment should be protected to the appropriate standard.

8.2.2 Personal protection: A suitable and sufficient COSHH assessment must be

undertaken and appropriate and compliant personal

protective equipment (PPE) provided and used.

Eye protection: Goggles or glasses giving complete protection to eyes

(EN 166) or face shield.

Skin protection: Appropriate barrier creams.

Hand protection: Chemical resistant gloves. (EN 374).

Other: Long sleeve protective clothing. Plastic apron. Rubber

boots.

Respiratory protection: In the case of insufficient ventilation, wear suitable

respiratory equipment.

Air-fed respiratory protective equipment should be worn when this product is sprayed, in addition to other

exposure-reduction measures (e.g. booth design).

### 8.2.3 Environmental exposure controls

Inform environmental manager of all incidents involving this product.

Version: 1.0 Product code: BT2 Page 8 of 14 Date: 06/01/2017





## **SECTION 9: Physical and Chemical Properties**

## 9.1 Information on basic physical and chemical properties

Appearance: Clear liquid
Odour: Solvent

Odour threshold:Not availablepH:Not applicableMelting/freezing point:Not availableInitial boiling point and boiling range:Not available

Flash point: 19°C (closed cup)

Evaporation rate:

Flammability (solid; gas):

Upper/lower flammability or explosive limits:

Vapour pressure:

Vapour density:

Not available

Not available.

Not available

Not available

0.82 (Water = 1)

**Solubility:** Partially miscible with water

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

Not available

Not available

Viscosity:

Not available

**Explosive properties:** Vapour may form explosive mixture with air

Oxidising properties: Not oxidising

9.2 Other information

None

## **SECTION 10: Stability and Reactivity**

**10.1 Reactivity** No specific reactivity hazards.

**10.2 Chemical stability** Stable under normal conditions.

**10.3 Possibility of hazardous reactions** No hazardous reactions expected during normal use.

Version: 1.0 Product code: BT2 Page 9 of 14
Date: 06/01/2017 Product name: Guncleaner/Degreaser





10.4 Conditions to avoid Keep away from sources of ignition, hot surfaces, direct

sunlight and other sources of ignition.

10.5 Incompatible materials Strong oxidising agents.

10.6 **Hazardous decomposition products** Combustion may liberate toxic smoke, fumes,

incomplete combustion products and oxides of carbon.

## **SECTION 11: Toxicological Information**

#### 11.1 Information on toxicological effects

**Acute toxicity** Harmful in contact with skin.

Harmful if inhaled.

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation Causes serious eye irritation.

Skin sensitisation Not classified. The product does not contain substances

classified as skin sensitisers above the classification

thresholds.

**Respiratory irritation** Vapour irritates the nose, throat and lungs.

Respiratory sensitisation No evidence of respiratory sensitisation.

Germ cell mutagenicity Not mutagenic.

Carcinogenicity Not carcinogenic.

Reproductive toxicity Not classified. The product does not contain substances

classified for reproductive toxicity above the

classification thresholds.

Specific Target Organ Toxicity - single

exposure

Inhalation of high concentrations of vapour may cause respiratory tract irritation, drowsiness or dizziness.

Specific Target Organ Toxicity -

repeated exposure

Prolonged or repeated inhalation of high concentrations

of vapour can cause damage to organs.

**Aspiration hazard** If ingested, may be aspirated into the lungs and cause

chemical pneumonitis

Version: 1.0 Product code: BT2 Page 10 of 14 Date: 06/01/2017





### Information on likely routes of exposure

**Inhalation** See above

Skin contact See above

Eye contact See above

**Ingestion** See above

Symptoms related to the physical, chemical

and toxicological characteristics

See above

Other information None

## **SECTION 12: Ecological Information**

**12.1 Toxicity** The product is low hazard for the environment.

The following data is for Xylene:

LC50 96h fish: 4.2. mg/l (*Onchorhynchus mykiss*) EC50 48h aquatic invertebrates: 2.9 mg/l (*Daphnia* 

magna)

EC50 72h aquatic plants: 4.4.mg/l (Pseudokirkneriella

subcapitata)

NOEC 96h fish early life stage: 3.3 mg/l (Menidia

menidia)

NOEC 48h aquatic invertebrates: 6.8 mg/l (Daphnia

magna)

**12.2 Persistence and degradability** Data for Xylene:

Readily biodegradable. Air photolysis: half-life 1.09 days. Transformation due to photolysis or hydrolysis not expected to be significant. Water degradation: 70% in

28 days; readily biodegradable in water.

**12.3 Bioaccumulative potential** Potential for Xylene to bioaccumulate is low. Log Kow

(octanol/water): 3.12 (calculated).

**12.4 Mobility in soil** The product contains volatile organic compounds (VOC)

which will evaporate easily from all surfaces.

12.5 Results of PBT and vPvB assessment Not classified as PBT/vPvB by current EU criteria.

Version: 1.0 Product code: BT2 Page 11 of 14

Date: 06/01/2017 Product name: Guncleaner/Degreaser





#### 12.6 Other adverse effects

No other adverse effects are expected.

## **SECTION 13: Disposal Considerations**

#### 13.1 Waste treatment methods

Product and packaging to be disposed of as hazardous waste. Disposal should be in accordance with local, state or national legislation.

Contaminated adsorbent must be removed in sealed, drums and disposed of via an authorised waste disposal contractor. Do not empty into drains; dispose of this material and its container in a safe way.

Empty containers may contain residue and may be dangerous. Do not attempt to refill or clean containers without proper instructions. Do not pressurise, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity or other sources of ignition. Residual flammable vapour may cause an explosion.

## **SECTION 14: Transport Information**

#### ROAD (ADR)

14.1	UN Number	1263

14.2 UN Proper shipping name PAINT RELATED MATERIAL

14.3 Transport hazard class(es) 3 14.4 Packing group Ш 14.5 Environmental hazards Nο

#### INLAND WATERWAYS (ADN/ADNR)

141	UN Number	1263
17.1	OII HUIIIDEI	1200

PAINT RELATED MATERIAL 14.2 UN Proper shipping name

14.3 Transport hazard class(es) 3 14.4 Packing group Ш 14.5 **Environmental hazards** No

Version: 1.0 Product code: BT2 Page 12 of 14 Date: 06/01/2017





## RAIL (RID)

**14.1 UN Number** 1263

**14.2 UN Proper shipping name** PAINT RELATED MATERIAL

14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards

#### AIR (IATA/ICAO)

**14.1 UN Number** 1263

**14.2 UN Proper shipping name** PAINT RELATED MATERIAL

14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards

#### SEA (IMDG)

**14.1 UN Number** 1263

14.2 UN Proper shipping name PAINT RELATED MATERIAL

14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards

14.6 Transport in bulk according to Annex II

of MARPOL 73/78 and the IBC code Not intended to be transported in bulk

## **SECTION 15: Regulatory Information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 1907/2006 as amended. The product has been classified in accordance with Regulation (EC) No. 1272/2008 (CLP).

**15.2 Chemical Safety Assessment** Not applicable.

Version: 1.0 Product code: BT2

Date: 06/01/2017 Product name: Guncleaner/Degreaser





## **SECTION 16: Other Information**

Full text of relevant H-statements: H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation. H336: May cause drowsiness of dizziness.

H373: May cause damage to organs through prolonged

or repeated exposure.

#### References:

Suppliers' Safety Data Sheets for components Regulation (EC) No. 1272/2008 EH40/2005, 2<sup>nd</sup> Ed., 2011

#### Disclaimer:

THE INFORMATION PRESENTED HEREIN IS BELIEVED TO BE ACCURATE. BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM, IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

#### **Version history:**

Version: 1.0

Issue date: 06/01/2017 **Previous Version:** Not numbered Issue date of previous version: February 1997

Sections changed from previous version: All sections reviewed and revised

Version: 1.0 Product code: BT2 Page 14 of 14 Date: 06/01/2017