

47-Line (Incl. 547-Line) - SBA

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** 47-Line (Incl. 547-Line) - SBA
Other means of identification:
Internal Reference Code: 10962
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Base for coatings. For professional users/industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Dacrylate Paints Limited
Lime Street, Kirkby in Ashfield
NG17 8AL Nottingham - United Kingdom
Phone: 01623 753845
- 1.4 Emergency telephone number:** +44 (0) 1623 753845 08:30-17:00 MON-FRI

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
It is advised that, due to the encapsulation of the active ingredient, it is estimated that inhalation hazards could be minimized. This criterion applies throughout the entire SDS.
GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):
Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).
Acute Tox. 4: Acute toxicity, Category 4, H312+H332
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Flam. Liq. 3: Flammable liquids, Category 3, H226
Skin Irrit. 2: Skin irritation, Category 2, H315
- 2.2 Label elements:**
Metals in massive form, alloys, mixtures containing polymers and mixtures containing elastomers do not require a label if they do not present a hazard to human health by inhalation, ingestion or contact with skin or to the aquatic environment in the form in which they are placed on the market, although classified as hazardous.
GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):
Warning
- 

- Hazard statements:**
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Skin Irrit. 2: H315 - Causes skin irritation.
- Precautionary statements:**
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P264: Wash thoroughly after use.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.
P403+P235: Store in a well-ventilated place. Keep cool.
P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.
- Supplementary information:**
EUH208: Contains Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compds. with amides from diethylenetriamine and tall-oil fatty acids. May produce an allergic reaction.
EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- Substances that contribute to the classification**

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA
SECTION 2: HAZARDS IDENTIFICATION (continued)

Xylene; Ethylbenzene

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS
3.1 Substance:

Non-applicable

3.2 Mixture:
Chemical description: Based mixed polymers, dispersants and organic and inorganic compounds

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 1330-20-7	Xylene Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	 25 - <50 %
CAS: 100-41-4	Ethylbenzene Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	 2.5 - <10 %
CAS: 128601-23-0	Hydrocarbons, C9, aromatics Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	 2.5 - <10 %
CAS: 108-88-3	Toluene Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	 <1 %
CAS: 222716-38-3	Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compds. with amides from diethylenetriamine and tall-oil fatty acids Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373 - Warning	 <1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
Xylene CAS: 1330-20-7	LD50 oral	Not relevant	
	LD50 dermal	1100 mg/kg (ATEi)	
	LC50 inhalation	11 mg/L (ATEi)	

SECTION 4: FIRST AID MEASURES
4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

The possibility of being inhaled is practically nil, however, in the case of symptoms:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA**SECTION 4: FIRST AID MEASURES (continued)**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA
SECTION 7: HANDLING AND STORAGE
7.1 Precautions for safe handling:
A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in The Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016 and with the minimum requirements for protecting the security and health of workers under the selection criteria of The Dangerous Substances and Explosive Atmospheres Regulations 2002, 2002 No. 2776. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:
A.- Specific storage requirements

Minimum Temp.: 5 °C
Maximum Temp.: 30 °C
Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
	WEL (8h)	50 ppm	220 mg/m ³
Xylene ⁽¹⁾ CAS: 1330-20-7	WEL (15 min)	100 ppm	441 mg/m ³
Ethylbenzene ⁽¹⁾ CAS: 100-41-4	WEL (8h)	100 ppm	441 mg/m ³
	WEL (15 min)	125 ppm	552 mg/m ³
Toluene ⁽¹⁾ CAS: 108-88-3	WEL (8h)	50 ppm	191 mg/m ³
	WEL (15 min)	100 ppm	384 mg/m ³

⁽¹⁾ Skin

Biological limit values:

BIOLOGICAL MONITORING GUIDANCE VALUES (BMGVs) - EH40/2005

Identification	NULL	NULL	NULL
Xylene CAS: 1330-20-7	1030 mg/g (NULL)	Methyl hippuric acid in urine	Post shift

DNEL (Workers):

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	180 mg/kg	Not relevant
	Inhalation	Not relevant	293 mg/m ³	77 mg/m ³	Not relevant
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	25 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	150 mg/m ³	Not relevant
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	384 mg/kg	Not relevant
	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	12.5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant
	Inhalation	260 mg/m ³	260 mg/m ³	65.3 mg/m ³	65.3 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Not relevant	Not relevant	1.6 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	15 mg/m ³	Not relevant
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral	Not relevant	Not relevant	11 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	11 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	32 mg/m ³	Not relevant
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Not relevant	Not relevant	8.13 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	226 mg/kg	Not relevant
	Inhalation	226 mg/m ³	226 mg/m ³	56.5 mg/m ³	56.5 mg/m ³

PNEC:

Identification					
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6.58 mg/L	Fresh water	0.327 mg/L	
	Soil	2.31 mg/kg	Marine water	0.327 mg/L	
	Intermittent	0.327 mg/L	Sediment (Fresh water)	12.46 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	12.46 mg/kg	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9.6 mg/L	Fresh water	0.1 mg/L	
	Soil	2.68 mg/kg	Marine water	0.01 mg/L	
	Intermittent	0.1 mg/L	Sediment (Fresh water)	13.7 mg/kg	
	Oral	0.02 g/kg	Sediment (Marine water)	1.37 mg/kg	
Toluene CAS: 108-88-3 EC: 203-625-9	STP	13.61 mg/L	Fresh water	0.68 mg/L	
	Soil	2.89 mg/kg	Marine water	0.68 mg/L	
	Intermittent	0.68 mg/L	Sediment (Fresh water)	16.39 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	16.39 mg/kg	

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply):	61.42 % weight
V.O.C. density at 20 °C:	672.81 kg/m ³ (672.81 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Appearance:	Not available
Colour:	Not available
Odour:	Not available
Odour threshold:	Not relevant *
Volatility:	
Boiling point at atmospheric pressure:	139 °C
Vapour pressure at 20 °C:	773 Pa
Vapour pressure at 50 °C:	4124.32 Pa (4.12 kPa)
Evaporation rate at 20 °C:	Not relevant *
Product description:	
Density at 20 °C:	1095.4 kg/m ³
Relative density at 20 °C:	1.095
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	>6000 mm ² /s
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *
Flammability:	
Flash Point:	29 °C
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	200 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available
Particle characteristics:	
Median equivalent diameter:	Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA
SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION
11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

It is advised that, due to the encapsulation of the active ingredient, it is estimated that inhalation hazards could be minimized. This criterion applies throughout the entire SDS.

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Xylene (3); Ethylbenzene (2B); Toluene (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); Titanium dioxide (2B); Mica (RCS < 1%) (1); Silicon dioxide (RCS > 10 %) (3); Reaction mass of ethylbenzene and xylene (3); Quartz (1 % < RCS < 10%) (1); Hydrocarbons, C9, aromatics (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Xylene CAS: 1330-20-7	LD50 oral	3523 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	
	LC50 inhalation	11 mg/L (ATEi)	
Ethylbenzene CAS: 100-41-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17.2 mg/L (4 h)	Rat
Toluene CAS: 108-88-3	LD50 oral	5580 mg/kg	Rat
	LD50 dermal	12124 mg/kg	Rat
	LC50 inhalation	28.1 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Ethylbenzene CAS: 100-41-4	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Hydrocarbons, C9, aromatics CAS: 128601-23-0	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
Toluene CAS: 108-88-3	LC50	5.5 mg/L (96 h)	Oncorhynchus kisutch	Fish
	EC50	3.78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	Not relevant		
Fatty acids, tall-oil, esters with polyethylene glycol mono (hydrogen maleate), compds. with amides from diethylenetriamine and tall-oil fatty acids CAS: 222716-38-3	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae

Chronic toxicity:

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA
SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration	Species	Genus
Xylene	NOEC 1.3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7	NOEC 1.17 mg/L	Ceriodaphnia dubia	Crustacean
Ethylbenzene	NOEC Not relevant		
CAS: 100-41-4	NOEC 0.96 mg/L	Ceriodaphnia dubia	Crustacean

12.2 Persistence and degradability:
Substance-specific information:

Identification	Degradability	Biodegradability
Xylene	BOD5 Not relevant	Concentration Not relevant
CAS: 1330-20-7	COD Not relevant	Period 28 days
	BOD5/COD Not relevant	% Biodegradable 88 %
Ethylbenzene	BOD5 Not relevant	Concentration 100 mg/L
CAS: 100-41-4	COD Not relevant	Period 14 days
	BOD5/COD Not relevant	% Biodegradable 90 %
Toluene	BOD5 2.5 g O ₂ /g	Concentration 100 mg/L
CAS: 108-88-3	COD Not relevant	Period 14 days
	BOD5/COD Not relevant	% Biodegradable 100 %

12.3 Bioaccumulative potential:
Substance-specific information:

Identification	Bioaccumulation potential
Xylene	BCF 9
CAS: 1330-20-7	Pow Log 2.77
	Potential Low
Ethylbenzene	BCF 1
CAS: 100-41-4	Pow Log 3.15
	Potential Low
Toluene	BCF 90
CAS: 108-88-3	Pow Log 2.73
	Potential Moderate

12.4 Mobility in soil:

Identification	Absorption/desorption	Volatility
Xylene	Koc 202	Henry 524.86 Pa·m ³ /mol
CAS: 1330-20-7	Conclusion Moderate	Dry soil Yes
	Surface tension Not relevant	Moist soil Yes
Ethylbenzene	Koc 520	Henry 798.44 Pa·m ³ /mol
CAS: 100-41-4	Conclusion Moderate	Dry soil Yes
	Surface tension 2.859E-2 N/m (25 °C)	Moist soil Yes
Toluene	Koc 178	Henry 672.8 Pa·m ³ /mol
CAS: 108-88-3	Conclusion Moderate	Dry soil Yes
	Surface tension 2.793E-2 N/m (25 °C)	Moist soil Yes

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS
13.1 Waste treatment methods:

Code	Description	Waste class
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

Type of waste:

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

HP14 Ecotoxic, HP3 Flammable, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



- | | |
|---|------------------------|
| 14.1 UN number: | UN1263 |
| 14.2 UN proper shipping name: | PAINT RELATED MATERIAL |
| 14.3 Transport hazard class(es): | 3 |
| Labels: | 3 |
| 14.4 Packing group: | III |
| 14.5 Environmental hazards: | No |
| 14.6 Special precautions for user | |
| Tunnel restriction code: | D/E |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 5 L |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | Not relevant |

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- | | |
|---|------------------------|
| 14.1 UN number: | UN1263 |
| 14.2 UN proper shipping name: | PAINT RELATED MATERIAL |
| 14.3 Transport hazard class(es): | 3 |
| Labels: | 3 |
| 14.4 Packing group: | III |
| 14.5 Marine pollutant: | No |
| 14.6 Special precautions for user | |
| Special regulations: | 163, 223, 955, 367 |
| EmS Codes: | F-E, S-E |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 5 L |
| Segregation group: | Not relevant |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | Not relevant |

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1263
14.2 UN proper shipping name: PAINT RELATED MATERIAL
14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

H312+H332: Harmful in contact with skin or if inhaled.

H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

- CONTINUED ON NEXT PAGE -

47-Line (Incl. 547-Line) - SBA**SECTION 16: OTHER INFORMATION (continued)**

Acute Tox. 4: H302 - Harmful if swallowed.
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
Acute Tox. 4: H332 - Harmful if inhaled.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Repr. 2: H361d - Suspected of damaging the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Irrit. 2: Calculation method
Aquatic Chronic 3: Calculation method
Acute Tox. 4: Calculation method
Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanol/water partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -