

**PRODUCT NAME**

Prep Clean 2806

**ORIGINALLY ISSUED**

22/09/2005

**VERSION**

1.0

**PRODUCT CODE**

DEG2806

**VERSION DATE**

22/09/2005



**PRODUCT DESCRIPTION**

A strong Preparatory Cleaning solvent for the degreasing of old u-PVC substrates.



**IMPORTANT INSTRUCTIONS BEFORE USE**

- Read and follow SDS, TDS and label instructions
- Stir all paints thoroughly before use
- Always use the same batch number on the same job
- Check colour & sheen. HMG will not accept any discrepancies arising after use
- Filter the product immediately before use
- Reduce emissions and maintain quality by replacing tin lid after use
- If in any doubt speak HMG Technical Service Department on (0161) 205 7631



**MAXIMUM VOC CONTENT (RFU)**

0.840K<sub>g</sub>/L

**REGULATIONS / COMPLIANCE**

- 2004/42 IIB (A) 850



**GENERAL INFORMATION**

Coverage	30 square metres per litre
Flashpoint	> 35°C
Storage	Store between 5°C - 25°C. When not in use, cans must be kept sealed
Shelf Life	12 months from delivery date in original sealed containers



**CLEANING**

Apply by cloth and quickly remove using clean lint free cloth.  
Repeat until surface is clean and free from all deposits (grease,oil,silicone).  
Replace cloths regularly to ensure that contamination is not re-applied to the surface.



**SURFACE PREPARATION**

Please refer to Knowledge Base for details on Surface Preparation.



**HEALTH AND SAFETY**

- Refer to SDS and tin label prior to use.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of HMG's knowledge and belief accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use. For professional use only.